Description

Method and communications device for adapting the data rate in a
communications device.

The present invention relates to a method in accordance with the
5   preamble of Claim 1 or 11 for adapting the data rate in a
communications device as well as to a corresponding communications
device in accordance with the preamble of Claim 16.

Different applications in communications systems mostly operate with
different data rates. But the underlying transmission channels
10   however mostly offer, because they are embedded into certain
transmission formats, only a fixed data transmission rate or a raw
data transmission rate or only a discrete set of such data rates. It
will thus be necessary in general to match the data rates to each
other at the corresponding interface. This is described below using
15   an example from the UMTS standardization:
At present work is in progress on standardizing what is known as the
UMTS (Universal Mobile Telecommunications System) mobile radio
standard for third-generation mobile radio devices. In accordance
with the known current state of UMTS standardization there is
20   provision for subjecting the data to be transferred via a high
frequency channel to channel coding in which case, convolutional
codes are used in particular. The data to be transmitted is coded
redundantly by channel coding which makes a more reliable retrieval
of the transmitted data possible on the receiver side. The code used
25   in each case for channel coding is characterized by its code rate r
= k/n, where k is the number of data bits or message bits to be
transmitted and n is the number of the bits present after encoding.
As a rule, the smaller the code rate the more powerful the coding. A

problem associated with coding is however that the data rate is
reduced by a factor of r.

Rate matching is performed in the transmitter to adapt the data rate
of the coded data stream to the relevant possible transmission rate
5   with bits being either removed from the data stream in accordance
with a specific pattern or duplicated in the data stream. The
removal of bits is the called 'puncturing' and the duplication is
called repetition.

According to the current status of UMTS standardization it is
10   proposed and that for rate matching an algorithm be used which
performs puncturing with an almost regular puncturing pattern, I eat
the bits to be punctured are distributed equidistantly over the
coded data block to be punctured in each case.

In addition it is known that for convolutional coding the bit error
15   rate (BER) decreases at the edge of a correspondingly coded data
block. It is also known that the bit error rate within a data block
can be changed locally by regularly distributed puncturing. It is
further known from WO 01/26273A1 and WO 01/39421 A1 that it is
advantageous to puncture the individual data blocks of the data
20   stream for adapting the data rate in accordance with a specific
puncturing pattern, in which case the puncturing pattern is designed
in such a way that it features a puncturing rate that increases
constantly from a middle area of the individual data block to at
least one end of the individual data block.

25   The object of the present invention is thus to specify a method for
adapting the data rate of a data stream in a communications device
as well as a corresponding communications device which guarantees a

satisfactory bit error rate and can be used in particular in mobile
radio systems with convolutional coding.

This object is achieved according to the invention by a method with
the features of Claim 1 and 16 or by a communications device with
the features of Claim 16. The subclaims define preferred and
advantageous forms of embodiment of the present invention.

In this case the methodology of convolutional codes will be used to
find heuristic puncturing patterns after the use of which all bits
of the punctured data block possess a bit error rate corresponding
to their relevant importance.

Preferably the puncturing pattern features a puncturing rate which
increases from the middle area to both ends of the relevant data
block. In this way the bits at the start and the end of the data
block to be punctured in each case are punctured more heavily where
this is done, not with an evenly-distributed puncturing rate, but
with any puncturing rate which essentially increases towards both
ends of the data block, i.e. the gap between the punctured bits is
on average ever shorter towards both ends of the data block. As will
be shown below the puncturing rate surprisingly does not have to
increase in a strictly monotonous way towards the ends, or expressed
in other terms, the puncturing gap does not have to decrease
strictly monotonously. Instead, because of the specific
characteristics of the convolutional codes used and in particular
the generator polynomials used, it can also be an advantage to use
somewhat more irregular patterns.

This puncturing leads to an evenly-distributed error rate of the
individual bits over the punctured data block and in addition

4

results in a reduced overall error probability.

The present invention is particularly suitable for adapting the data
rate of a convolutional coded data stream and can thus preferably be
used in UMTS mobile radio systems, in which case this relates both
5   to the area of the mobile radio transmitter and to the mobile radio
receiver. The invention is however not restricted to this area of
application but can be used in general wherever the data rate of
data stream is to be adapted.

The present invention will be described below in greater detail with
10   reference to the enclosed drawing using preferred exemplary
embodiments.

Fig 1: a simplified block diagram of a mobile radio transmitter in
accordance with the invention.

Fig 2: the bit error rate BER per bit for puncturing in accordance
15   with an exemplary embodiment at HS-SCCH, Part 2, coding with R=1/3
with a ratio of the energy of the transmitted bits to the noise
power density E_3/N_0 = - 2 dB. The HS-SCCH channel stands for the
high-speed shared control channel via which specific configuration
information is transferred and which can the subdivided into two
20   subareas, known as Part 1 and Part 2. Part one is transferred first
in this case and contains the information which the mobile station
requires first in order to process the following data channel. Part
2 contains that information which the mobile station does not need
until later. What this division into two parts achieves is to make
25   the delay through the HS-SCCH as small as possible simce only the
first part has to be decoded before data can begin to be received.

Fig. 3: the bit error rate BER per bit for the rate matching
proposed in UMTS (Specification 25.21. v5.0.0, chap. 4.2.7 'Rate

Matching') for HS-SCCH, Part 2, for a ratio of the energy of the transferred bits to the noise power density $E_3/N_0 = -2$ dB.

Fig. 4: a comparison of the results which can be achieved with puncturing in accordance with the invention (upper curve, crosses) or a conventional puncturing (lower curve, circles) as regards the resulting overall error probability, where the diagram shows the probability that least one bit of a block has been transmitted incorrectly (known as the frame error rate).

Fig. 5: underlying schemes for convolutional codes in UMTS

Fig. 6: the bit error rate BER per bit for the rate matching proposed in UMTS (specification 25.21. v5.0.0, chap. 4.2.7 'Rate Matching') for HS-SCCH, Part 1, for a ratio of the energy of the transferred bits to the noise power density $E_3/N_0 = -3$ dB.

Fig. 7: how many input bits are involved for a puncturing of one output bit In the various output stages Output 1, Output 2 and output 3.

Fig. 8: which input bits (bit numbers) are affected by the puncturing.

Fig. 9: a table with the results of the puncturing depending on the number of punctured bits.

Fig. 10: the bit error rate BER per bit for a puncturing in accordance with an exemplary embodiment for HS-SCCH, Part 1, for a signal-to-noise ratio of the energy of the transferred bits for a noise power density of $E_3/N_0 = -3$ dB.

Fig. 11: different exemplary embodiments for a puncturing of 8 bits (48 to 40 bits) for an encoding with a rate 1/3

Fig. 12: different exemplary embodiments for a puncturing of 31 bits (puncturing from 111 to 80 bits), R = 1/3

5   Fig. 13: different exemplary embodiments for a repetition of 31 bits (repetition from 32 to 40 bits) R = 1/2

Fig. 14: different exemplary embodiments for a repetition of 6 bits (74 to 80 bits), R = 1/3

Fig. 15: different exemplary embodiments for a repetition of 4 bits
10   (36 to 40 bits), R = 1/2

Fig. 16: different exemplary embodiments for a repetition of 14 bits (54 to 40 bits), R = 1/3

Fig. 17: further exemplary embodiments for a puncturing of 31 bits (puncturing from 111 to 80 bits), R = 1/3. This figure can also be
15   viewed as a continuation of Fig. 12

Fig. 18: an exemplary embodiment for a puncturing from 108 to 80 bits, R = 1/3

Fig. 19: exemplary embodiments for puncturing from 114 to 80 bits, R = 1/3

20   Fig. 20: exemplary embodiments for puncturing from 117 to 80 bits, R = 1/3

Fig. 21 exemplary embodiments for puncturing from 52 to 40 bits, R = 1/2

Fig. 22 exemplary embodiments for puncturing from 46 to 40 bits, R =
1/2

Fig. 23 exemplary embodiments for puncturing from 54 to 40 bits, R =
1/3

Fig. 24 exemplary embodiments for puncturing from 56 to 40 bits, R =
1/2

Fig. 25 exemplary embodiments for repetition from 36 to 40 bits, R =
1/2

Fig. 26 exemplary embodiments for puncturing from 48 to 40 bits

Fig. 27 exemplary embodiments for puncturing from 11 to 40 bits

FIG. 28: Rate matching specifications from the 3 GPP Spcification
25.211 v5.0.0, Chap. 4.2.7 Rate matching

In general the rows in the table with all bold numbers mean the
relevant especially preferred exemplary embodiment, in which case
however the quality of the other exemplary embodiment does not
necessarily differ in any major way from this highlighted examplary
embodiment. In Figures 26 and 27 however figures entered in bold
indicate the bits punctured or repeated by the described
construction principle of the rate matching formula in accordance
with invention at the start or the end of the repetition pattern.
These are defined such that, by contrast, the position of the bits
not shown in bold type can easily be shifted by variation of the
parameter or within the framework of this invention (typically by
one position).

Fig. 1 shows a schematic diagram of the structure of the mobile
radio transmitter 1 in accordance with the invention and from which
data or communications information, especially voice information,
will be transmitted via a high-frequency transmission channel to the
5   receiver. In Fig. 1 the components involved in the coding of this
information or data are shown in particular. The information
provided by a data source 2, for example a microphone, is initially
converted with a digital source coder 3 into a bit stream. The
voice-coded data is subsequently coded with the aid of a channel
10   coder, in which case the actual payload or message bits are coded
redundantly which allows transmission errors to be detected and
subsequently corrected. The channel coder 4 can be a convolutional
coder. The code rate produced for channel coding r is an important
variable to describe the codes used in each case for channel coding
15   and is, as has already been mentioned, defined by the expression r
k/n. in this expression the k stands for the number of data bits and
n for the total number of bits coded. i.e. the number of inserted
redundant bits corresponds to the expression n – k. A code with the
code rate r defined above is also referred to as an (n,k) code, in
20   which case the performance of the code increases with a decreasing
code rate r. For channel coding so-called block codes or
convolutional codes are normally used.

The following explanations are based on the assumption that – as
defined in the current state of UMTS standardization – convolutional
25   codes are used for channel coding. A major difference to block codes
is that with convolutional codes individual data blocks are not
coded consecutively but that a continuous processing is involved, in
which case each current code word of an input sequence also depends

9

on the previous input sequence. Independently of the code rate r =
k/n convolutional codes are also characterized by what is known as
the constraint length K. The constraint length specifies over how
many clock pulses of k new input bits of the channel coder 4 a bit
5   influences the code word output by the channel coder 5.

For UMTS the following convolutional codes are used, as shown in
Figure 5. The figure is taken from specification 25.212, Chap.
4.2.3.1 "Convolutional coding".

Before transmission of the channel-coded information to the receiver
10   this information can be routed to an interleaver 5 which reorders
the bits to be transmitted in accordance with a specific scheme and
thereby spreads them over time in which case the errors which as a
rule occur in bundles are distributed in order to obtain what is
known as a memoryless transmission channel with a quasi-random error
15   distribution. The information or data coded in this way is routed to
a Modulator 7 which has the task of modulating the data onto a
carrier signal and of transmitting in accordance with a prespecified
multiple access method via a high-frequency transmission channel 3
to a receiver.

20   For transmission the coded data stream is subdivided into data
blocks, in which case the channel coder 4 is set to a known status
at the beginning of a data block. At the end each coded data block
is terminated by what are known as tail bits so that the channel
coder 4 is again in a known state. The result of this convolutional
25   code and channel code 4 structure is that the bits at the start and
end of a coded data block are better protected from transmission
errors than those in the middle of the block. In this case it is of

no significance whether these tail bits all have the known value of
0 or whether they have another value. Random values can also be
chosen for these tail bits, in which case both transmitter and
receiver must know the values to be used.

5   The error probability of a bit differs depending on its position
within the relevant data block. This effect is exploited for example
in voice transmission in GSM mobile systems by placing the most
important bits of the block at both ends where the error probability
is at its lowest. With data transmissions however data packets are
10   already rejected if just one single transmitted bit is in error
which can for example be established in the receiver by a 'Cyclic
Redundancy Check' (CRC). Here it is thus not possible to refer to
important or less important data in a data transmission, all bits
being regarded as equally important. If errors occur in a control
15   block, that is a data block which contains control information which
contains information about how subsequent payload data is to be
encoded and transferred, then in general correct detection of this
payload data is even then no longer possible if just a single bit is
received incorrectly, since the received data is then interpreted
20   incorrectly.

To match the data rate of the coded data stream to the relevant
transmission rate possible the rate matching is performed before the
modulator 7. For the exemplary embodiment shown in Fig 1 rate
matching is undertaken in the rate matching unit 6b, in which case
25   the puncturing unit 6a first undertakes puncturing in accordance
with a specific puncturing pattern in order to achieve a more equal
error distribution over a data block. The execution sequence of the
puncturing unit 6a shown in Fig 1 as well as of the interleaver are

merely to be taken as examples. The interleaver can also be arranged
after unit 6b. likewise the interleaver 5 can also be replaced by
two interleavers before and after the rate matching unit 6b etc.

It is also an object of this invention to further optimize
5   puncturing patterns and especially match them to the polynomials
used for the channel coder. There is also the task, depending on the
convolution code used (including the polynomials used) and the block
length, of selecting the quantity of bits to be punctured or
repeated so that the decoding is undertaken as favorably as
10   possible. As a rule a large number of options are produced so it is
at least very time and resource-consuming to develop a very good
rate matching pattern purely through simulation. If for example one
wishes to investigate all the options for puncturing of 48 bits to
40 bits this would be 48!/(8!*40) = 377348994 different options
15   which could not be investigated within a reasonable time.

This problem is especially evident for short block lengths such as
for example for the control information of the UMTS expansion HSDPA
and there in particular the HS-SCCH (high speed shared control)
channel. This cannel transmits configuration information which
20   specifies how the actual payload data sent over the specific data
channel is coded and further details, for example the spread codes
used for transmission. By contrast to the data channel over which a
large amount of data can be transmitted, this is a comparatively
small amount of data. In UMTS convolution codes with the rate 1/2 or
25   1/3 are used for coding, The polynomials used are shown in Fig. 5.
Also referred to as polynomials are the exact design of the 'tapping
points' i.e. which delay stages are tapped for the individual output
bit streams and logically combined by an exclusive OR operation.

12

The invention is thus especially applicable to what is known as the HS-SCCH (high speed shared control) channel.

The definition of the coding of the HS-SCCH is given in accordance with the current prior art in Specification 3GPP TS 25.1.212 V5.0.0

5   (2002-03) "Multiplexing and Channel Coding (FDD) (Release 5)", especially in Chapter 4.6 "Coding for HS-SCCH". This specification is abbreviated elsewhere in this Patent Application to 25.212. Subsection 4.6.6 "Rate Matching for HS-SCCH" defines that rate matching must be performed in accordance with the standard rate

10   matching algorithm in Chapter 4.2.7 "Rate Matching" which essentially effects an equidistant (as possible) puncturing or repetition.

The block length of the two parts of the HS-SCCH amounts in the current version to 8 bits for the first part, or if the tail bits

15   are included, 16 bits, 29 bits for the second part, or if the tail bits are included, 37 bits. Since the specification is still fluid modifications to various parameters or other block lengths can be produced. Furthermore the convolution codes with the rate 1/2 or 1/3 also come into the picture. The following rate matchings are

20   particularly relevant:

a) 32 to 40 (with code rate R = 1/2), or

b) 48 to 40 (with code rate R = 1/3), and

c) 74 to 80 (with code rate R = 1/2), or

d) 111 to 80 (with code rate R = 1/3).

25   **Method for determining puncturing and repetition patterns**

In overview it can thus be stated that for a rate matching a puncturing and/or repetition or also a repetition alone is

undertaken so that the overall bit error rate (BER) becomes minimal. To this end let us first look at the situation shown in Fig. 3: This records the bit error rate for the individual bits in a frame. The axis reflects the index or the relevant bit (frame index). One can

5   clearly see that the first and last bits feature a lower bit error rate. This can be understood in conjunction with the scheme for con volution codes from Figure 5: for transmission bits from the various delay stages D of the decoder are linked together by the convolution code in each case. The first bits are for example then also linked

10   with the bits preceding them, at bits which do not actually exist. These "non-existent bits" are then set to a known value, mostly zero. This is known to the receiver which on its side now decodes with these bits set to zero the first bits transmitted. Decoding is very secure here since one part of the bits is known with absolute

15   certainty.
     The same is true for the last bits: These are again followed by artificial bits, known as the tail bits, into which the delay elements D of the decoder are inserted; these tail bits are in their turn set to a known value, mostly zero.

20   In the middle area bits are linked together for which the value is not known with certainty at the receiver. This means that on decoding there is a greater probability of an error occurring, which expresses itself in a higher bit error rate.

     The envelope curve of the bit error rate in relation to the frame
25   number is thus initially deformed upwards in a convex shape for equal repetition or puncturing. There are now various options for how the envelope curve changes when the puncturing (or repetition) is changed.

14

a) <u>the envelope essentially represents a horizontal (or approximates to one)</u>

This means that the bit error rate is essentially the same for all bits within a frame. This occurs for example when there is

5   puncturing at the edges or repetition in the middle, or both, depending too on the rate to be matched.

b) <u>envelope curve has a concave shape</u>

In this case for example puncturing has been so heavy at the edge that the bits in the middle area of the frame exhibit a lower bit

10   error rate. This situation can be seen in Fig. 2.

c) <u>the bit error rate is irregularly distributed in relation to the frame number.</u> This case is not examined in any more detail here for the reasons given below.

The information given below relates to puncturing. Similar

15   considerations can be applied to repetition or for a combination of puncturing and repetition.

There are now very many options for how individual bits can be punctured. If for example one wishes, as already stated previously, to investigate all the possible options for puncturing 48 bits to 40

20   bits, this would be 48!/(8!*40!) = 377348994 different options, which cannot all be investigated within a reasonable time.

The aim is thus to eliminate non-viable options in advance. This is not done by random repetition and/or puncturing, which is why alternative c) will not be considered any further here.

25   An ordering principle is shown in Figure 7. For the first 9 input bits 1-9 as well as for the last 9 input bits n-8 to n the

puncturing level for the relevant output stage Output 0, Output 1,
Output 2 is illustrated. The output stages themselves, as can be
seen from Fig. 5, are the relevant output function which is formed
from all input bits preceding the input bit currently under

5   consideration in time. Here the output stages of Fig. 5b are
considered, that is the rate 1/3 convolutional encoder.
For puncturing with as little loss of information as possible it
makes sense to initially leave out bits (puncturing) which have
little influence on other bits. The puncturing level thus specifies

10 how many bits will be affected by puncturing of the bits concerned.

A typical methodology for leaving out or puncturing of bits is shown
in Figure 8. In the first column the first 9 input bits 1-9 are
again specified, as well as the last 9 input bits n-8 to n. In the
following columns the bit numbers of the information bits affected

15 by puncturing, that is information bits or input bits for the
relevant output stage output 0, output 1 and output 2 are shown. The
table fields are - as already in Fig 7 - set against an increasingly
darker background for an increasing number of information bits
influenced. The bits belonging to the light table fields are thus

20 candidates for puncturing.

Figure 9 shows a table in which the most important variables for
puncturing in the vicinity of the ends, that is puncturing of the
first and last bits, are illustrated. n input bits (information
bits) and k coded bits (bits at the output stage, output bits) are

25 considered. In the first column the number of punctured output bits
(# punct bits) is specified, in the last column, the (cumulative)
number of the bits affected by these bits at the input, in which
case input bits which are affected a number of times, that is by the
puncturing of a number of output bits, are also counted multiple

30 times accordingly.

In the second column Sequence specifies which output bit (bit number) has been punctured in this step. In this case the puncturing takes place beginning with the least important bits in the first row through to the following bits in the following rows. The entire puncturing pattern for 7 bits to be punctured for example is thus produced from the bits specified in column 2 in rows 1 through 7, that is bits 1, k, 4, k-4, k-6, 2, k-1. This pattern thus comprises the bits 1, 2 4, k-6 k-4, k-1, k.

Above the first row is the indexing for the first information bits 1-9 as well as the last information bits k-8 through k. For reasons of space this is written as just -8 etc. instead of k-8. The entries in the columns under the indexing of the information bits specify how greatly the relevant information is affected by the puncturing of the output bits which are specified in the 2^{nd} column up to the relevant row and are thus punctured. This means how many of the punctured output bits were linked to this information bit. This is a measure of how greatly the information bit involved was weakened by puncturing.

In the last column (cumulative) finally the sum of these effects is given. It is called the cumulative puncturing strength in this case.

The column average value gives the ratio V of the sum of the last column divided by the number of information bits involved. For example for 6 punctured bits $V=(2+1+1+1+1)/(1+1+1+1+1) = 1.2$. The average puncturing rate (av. puncturing rate) is the column 'average value' divided by 18, the total number of exclusive OR operations occurring per information bit during encoding.

A procedure for puncturing any given number of bits comprises preparing tables similar to the ones given above. The tables shown can be used for the rate 1/3 and the polynomials of the

convolutional encoder considered. For other encoding rates and/or
other polynomials the tables can be determined in a very similar
way. With the aid of these tables a puncturing sequence is
established in which first those output bits are punctured which
5   only have a small effect on the cumulative puncturing strength. If
there are a number of alternatives in these cases those bits which
minimize the maximum of the puncturing strength of the individual
bits are preferably punctured.
For a higher number of bits to be punctured and/or greater block
10   lengths as a rule the information from the tables must be combined
with the idea of achieving as equal as possible a distribution over
the entire block. It then makes sense to explicitly adopt additional
bits in the middle part which are generated by the generator
polynomials with the lowest powers, i.e. with the fewest logical
15   combinations. At the same time it should be ensured that the overall
distribution of the puncturing strengths in the middle area of the
frame does not exhibit any obvious peaks.

The same applies to repeating, but with the reversed leading signs.
This means that bits which were first punctured in accordance with
20   the heuristic and even a repetition is first performed in the middle
part, preferably by the polynomials of the most logical
combinations. Afterwards those bits are repeated at the edge which
(for puncturing) have as great as possible an influence on the
cumulative puncturing strength.

25   By contrast with methods in which the puncturing rate constantly
increases up to the ends, this leads to a result which is not
expected per se, since one would expect that the reliability of the
coded bits constantly decreases towards the ends. a closer
examination for the convolutional encoders used however shows that
30   this assumption is surprisingly not true. The specific

18

characteristics of the polynomials produce coded bits, particularly
at the ends, which contribute less effectively to the coding. These
bits however do not occur up to the end in constantly increasing
volumes, but are somewhat irregularly distributed. By aligning the
puncturing patterns specifically to these "weak" bits, that is by
giving preference to puncturing these bits, one can improve the
coding even further.
The invention thus makes use of an heuristic method which allows:

- The effect of the puncturing/repeating of a coded bit on the
  underlying information bits to be approximated by means of a
  newly-defined heuristic metric

- Specific bits to be selected explicitly and for each convolution
  code which are to be punctured or repeated,

- The number of the rate matching patterns to be investigated to be
  greatly restricted.

After a number of promising rate matching patterns have been
determined based on this method, these will be compared on the basis
of the frame error rate and the bit error rate of each individual
information bit (referred to hereafter as the bit error rate
distribution). The rate matching pattern can then be iteratively
further refined and optimized, based on the developed metric. The
bit error rate distribution of the non-punctured/non-repeated blocks
serves as start information.

The puncturing strength S_i per bit information bit i will be defined
as heuristic metric as the number of logical operations not
transmitted by puncturing of one information bit with the relevant
output bits of the encoder. S_i is thus positive for puncturing. For
repetition $S_{i,k}$ = n-1 is defined for each logical operation
transmitted n times.

19

S_{max} is the maximum possible puncturing strength specified by the code-specific total number of existing logical operations:

A good rate matching pattern is searched for in accordance with the following quality criterion:

5   1. select the cumulative puncturing strength to be close to the possible minimum

2. ensure that there is as even as possible a distribution of the bit error rate across all information bits

For the selection of the bits to be punctured/repeated, tables will

10   be set up based on the generator polynomials of the codes for the start and the end of the coded blocks which represent the cumulative puncturing strength per coded bit as well as the information bits concerned. This allows the coded bits to be divided into what are known as classes of the cumulative puncturing strength.

15   In accordance with the above quality criterion these tables are now used to search for bits to be punctured/repeated in such a way that initially, for those information bits which exhibit a lower bit error rate than other bits, the puncturing strength is increased and simultaneously the cumulative puncturing strength is kept low. The

20   puncturing strength will thus be selected to be inversely proportional to the bit error rate of the information bit and in addition bits will be explicitly sought which contribute little to the cumulative puncturing strength.

This method will then be applied iteratively, based on the first

25   pattern determined, so that, even after just a few simulations, a specifically optimized rate matching pattern can be found for the relevant convolution code.

Fig. 11 and 12 show different options for puncturing patterns in accordance with the invention, in which case the number of bits to be punctured (counting begins at one) is specified in each case. The tables are specified for different numbers of information bits to be

5   transmitted and different numbers of bits to be transmitted after the rate matching.

Fig. 3 typically shows the graph of the bit error rate for the individual bits transmitted of a data block depending on their position or location in the data block for a conventional puncturing

10   with a regular puncturing pattern.

Fig. 2 shows this graph for puncturing in accordance with the invention with pattern and number 33 from Fig. 12 which has shown itself to be particularly suitable in simulations. It can be seen from Fig. 2 that by using the puncturing pattern in accordance with

15   the invention a more even curve of the bit error rate over the entire data block can be achieved. Since in the middle area of the data block puncturing is less frequent compared to the conventional method, a lower error probability can be obtained there. Actually the error rate now rises slightly towards the ends which could

20   appear unfavourable at first glance. The result of this is however that there are many 'weak' bits at the edge, as already stated above, where puncturing can be performed very effectively.
Fig. 4 records the curve of the overall error rate over the ratio of the energy of the transmitted bits to the noise power density for

25   the same cases. It can be seen from Fig. 4 that with the aid of the invention (lower curve, circles) compared to the conventional method (upper curve, crosses) a frame error rate improved by around 0.2 dB can be achieved.

Similar improvements can also be achieved for other parameters. For example Fig. 6 shows the graph of the bit error rate for the individually transmitted bits of a data block depending on their position in the data block for a conventional puncturing with a

5   regular puncturing pattern for an encoding with a rate 1/3 and a puncturing of 8 bits (48 to 40 bits). This corresponds to a transmission of 8 input bits. Fig. 10 shows the distribution, if instead of this the puncturing pattern No. 3 from Fig. 11 is used which has also proved particularly suitable in simulations. It can

10   be seen that here a very evenly balanced distribution is produced. Here too an improvement is achieved of around 0.2 dB (but no curve is shown for this since it does not provide any further insights). Figure 16 shows further preferred exemplary embodiments as part of the invention with a puncturing of 14 of 54 bits in which case the

15   patterns 3 and 4 produce the best results.

Figures 13, 14 and 15 show preferred repetition patterns which are also obtained using the rules shown in this invention.

The present invention has previously been described on the basis of use in a mobile radio transmitter. The invention can of course also

20   be extended to mobile radio receivers where, for matching the data rate in the way described above, punctured or repeated signals must be processed in accordance with the puncturing or repetition pattern used in each case. In this case in the relevant receiver for bits punctured on the transmit side or repeated bits additional bits are

25   inserted into the received bit stream or two or more bits of the receive bit stream are grouped together. For insertion of additional bits, a flag is simultaneously set in the form of a soft decision to indicate that its information content is very uncertain. The

processing of the receive signal can be undertaken in the relevant
receiver in the same way in reverse order to Fig 1.

**Further bit adaptation patterns determined using the method
explained above**

5   The puncturing patterns specified previously predominantly
concentrate on puncturing in the end areas and/or repetition in the
middle area.

The further rate matching patterns now described were determined in
the previously explained method for different proposals for HS-SCCH
10   coding in the standardization. The bits to be punctured or to be
repeated are specified in each case. The bits are numbered
consecutively from 1 through N. The preferred pattern is given first
in each case, the further patterns however always exhibit similar
favourable characteristics.
15   Figure 17, in which these further puncturing patterns are listed,
thus represents an expansion of Figure 12. Accordingly puncturing
patterns for various output bit rates are shown in Figures 18-24 and
further repetition patterns in Fig. 25.

Approximation of preferred rate matching patterns using components
20   **already specified in the UMTS**

The patterns previously shown have the aim of proposing an optimum
possible selection of bits to be punctured or to be repeated, in
which case no other restrictions are imposed as regards the pattern.
In practical implementations however it can be of advantage to only
25   consider those patterns which can be implemented with the least
possible changes to existing rate matching circuits. A corresponding

rate matching specification is described in document Specification
25.212 v5.0.0 Chap 4.2.7 it "Rate Matching" which has already been
mentioned. The sections below will reflect the sense of the part of
this specification which undertakes the actual puncturing or
repetition and which is described in Chapter 4.2.7.5 "Rate matching
pattern determination".
Extract from the specification

Before rate matching the bits are identified by $x_{i1}, x_{i2}, x_{i3}, \ldots x_{ix}$. In
this case i stands for the transport channel number, the sequence
itself is defined in sections 4.2.7.4 of the Specification for the
uplimk and in 4.2.7.1 for the downlink. An uplink is taken to mean a
connection from a communications device to the base station, a
downlink a communication from a base station to a communications
device.

The rule for rate matching is reproduced in the section of the
program shown in Fig. ??? which runs when the condition is fulfilled
that puncturing has to be performed.
   - first an error value e is set to an initial value which lies
   between the original error value and the desired puncturing rate.
   - In a loop with the index m of the bit currently considered as
   run parameter, up to the end of the sequence, that is up to index
   X_i
      - the error value e his initially set to e – e_{minus}, where e_{minus}
      essentially represents the number of bits to be punctured.
      - A check is then made as to whether the error value e <= 0.
      - In this case a check is made as to whether the bit with
      the index m is to be punctured, in which case a bit to be
      punctured is then set to a value of δ which is other than 0
      or 1.

24

Where a repetition is to be undertaken essentially the same
procedure is performed, in which case a repeated bit is then set
directly after the original bit.

For puncturing the execution sequence then proceeds with the bits
5   which have been set to the value δ being removed so that these bits
are thus punctured

The parameters X_i, e_{ini}, e_{plus} and e_{minus} are selected so that the
desired rate you matching can be achieved. Essentially this means
that $e_{plus} = X_i$, $e_{minus} = N_p$, where X_i is the number of bits before rate
10   matching and N_p is the number of bits to be punctured or repeated.
e_{ini} can be chosen in the range between 1 and e_{plus}, which produces a
slight shift in the pattern, bits being used in specific cases (rate
matching after a first interleaving), to shift the patterns in
different frames suitably in relation to one other. The parameter i
15   identifies different transport channels in the Specification. This
parameter is however irrelevant in this case and is thus omitted.
Options are shown below for how one can approximate preferred rate
matching patterns for short block sizes with convolution codes using
this existing rate matching algorithm. In this case an attempt is
20   made under the general conditions of this algorithm to preferably
use bits at the end of the code block for puncturing and for
repetition to above all use bits from the middle of the code block.
A core aspect of this exemplary embodiment is not to limit the
parameter e_{ini} to the range of values from 1 to e_{plus}, but instead to
25   advantageously select it outside this range. Such a choice may
appear contradictory at first glance since it no longer ensures that
the desired number of bits are punctured or repeated. Through an

advantageous matching of the values of e_{plus} and e_{minus} however it is possible to the still achieve the desired number.

Let

X_i: Number of bits before rate matching

N_p: Number of bits to be punctured/repeated (the index p in N_p refers to the number are of bits to be punctured, N_p can however also designate the number of bits to be repeated.

To fully specify the use of the rate matching algorithm and their bike the rate matching pattern the initial error value e_{ini}, the error increment e_{plus} and the error decrement e_{minus} must be specified, since these parameters completely describe the rate matching pattern.

The paragraphs below illustrate the preferred rate matching patterns using the rate matching algorithm given in release 99 UTMS.

Subsequently options are shown for how the preferred rate matching patterns already present in the standard rate matching algorithm (data rate matching algorithm) can be approximated for short block sizes with convolution codes. In this case an attempt is made under the general condition of this algorithm for puncturing to preferably use bits at the ends of the code block and for repetition to above all use bits from the middle of the code block.

Puncturing

The parameters of the rate matching algorithm are selected so that the first N0 bits at the beginning of the code block are punctured, meaning that the following equation must apply

$$N_0 \cdot \left(e_{\min us} - e_{plus}\right) < e_{ini} \leq N_0 \cdot e_{\min us} - \left(N_0 - 1\right) \cdot e_{plus} \qquad (1)$$

There is provision as a further criterion for the last bit of the
block to be punctured as well, this being done in accordance with
the following condition:

$$(N_0 - 1) \cdot (e_{\min us} - e_{plus}) < e_{ini} \qquad (2)$$

5   In this case the value of the error variable e will actually be
negative precisely for the last bit which means that this bit is
then punctured.
Both criteria are for example fulfilled by the following preferred
selection of parameters:

10   $$e_{plus} = X_i - N_0 \qquad\qquad (3)$$

$$e_{\min u} = N_p - N_0 \qquad\qquad (4)$$

$$e_{ini} = N_0 \cdot e_{\min us} - (N_0 - 1) \cdot e_{plus} \qquad (5)$$

Also included in these formulae is the special case in which no bit
at the beginning of the code block is to be punctured ($N_0 = 0$). Then
15   the following applies: $e_{ini} = X_i$, $e_{plus} = X_i$, $e_{minus} = N_p$.   .

The general implementations which select e_{ini} in accordance with the
formulae (1) to (4) produce frame matching patterns which differ
from those in the preferred selection of parameters in accordance
with (3) to (5) merely in that from the (N_0 + 1)th up to the (N_p -
20   1)th puncturing point the index of the bits to be punctured can be
decremented by one.

For the application example of puncturing of 48 bits to 40 bits the
table in Fig. 26 shows puncturing patterns in accordance with the
preferred parameter selection up to $N_0 = 6$. The puncturing points not
25   printed in bold type can be decremented by one either partly or
completely by variation of the e_{ini} value in accordance with (1) and
(2).

The table shown subsequently in Fig. 27 shows in the same manner the resulting pattern for a puncturing of 111 bits to 80 bits.

Although this does not allow the optimum puncturing patterns which have already been discussed above to be achieved, it is still
5   possible to achieve a certain improvement of the transmission quality compared to the current status of the specification, in which case the changes to be made are comparatively small.

Repetition

The parameters of the rate matching algorithm are calculated in
10 accordance with the invention, so that a maximum gap between the last bit to be repeated and the block end is guaranteed, so that the following must apply:

$$e_{ini} = 1 + X_i \cdot e_{min\,us} - N_p \cdot e_{plus} \qquad (6)$$

Furthermore the average gap between bits to be repeated R_R can be
15 prespecified. R_R does not have to be a whole number but can be a positive rational number. The following then applies:

$$R_R = \frac{e_{plus}}{e_{min\,us}} \qquad (7)$$

This means that e_{plus} and e_{minus} can be freely selected under the general condition that their quotient produces precisely R_R and in
20 total N_p bits are to be repeated.

If the first bit to be repeated, or to put it more precisely, the position of the first bit to be repeated (designated here as b_1) is to be prespecified, the following equation must apply in addition to (6)

$$\frac{e_{ini}}{b_1} \le e_{min\,us} < \frac{e_{ini}}{b_1 - 1}, \qquad (8)$$
25

where e_{minus} should be a whole number and $b_1 \le X_i - N_p + 1$.

28

A preferred parameter selection is produced for

$$e_{\min us} = N_p \cdot \qquad\qquad (9)$$

$$e_{plus} = X_i - b_1 + 1 \qquad\qquad (10)$$

$$e_{ini} = (b_i - 1) \cdot N_p + 1 \qquad\qquad (11)$$

5   With this selection of parameters the position of the first bit to
be repeated is b_1 and, as required N_p bits are repeated.

Here too the repetition patterns produced are not optimal compared
to the patterns already discussed above. Despite this it is still
possible to achieve a certain improvement in transmission quality
10   with this method compared to the current state of the specification,
in which case the changes to be made are again comparatively small.
By selecting parameter b_1 well it is possible to achieve repetition
which does not begin right at the start. At the start repetition is
not actually needed since the bits at the start of the convolution
15   decoder as shown above in any event exhibit a comparatively low
error rate. It is thus far more beneficial when the bits to be
repeated, as occurs with this method, are concentrated further
towards the middle. A disadvantage of this exemplary embodiment
however is that it only avoids repetition at the beginning, with the
20   circumstances at the end far less able to be positively influenced.
That is the price which has to be paid for a simplified
implementation.

Of course combination of the criteria given above is also possible
for the selection of a puncturing pattern. For example one can
25   combine a pattern from two of the patterns presented here by using
the start of one pattern at the start and the end of the second
pattern at the end. Furthermore it makes no difference if the bits
are output in a changed sequence and at the same time the puncturing

pattern is adapted accordingly. For example the sequence of the
polynomials in the convolution coder can be swapped over.